



// **FEATURES**

- ❑ Reprogramming of all SimonsVoss locking devices in System 3060 using a Windows tablet
- ❑ Compact solution for reprogramming locks at the door
- ❑ Supports all SimonsVoss product generations and reader technology
- ❑ Supports all SimonsVoss product types (including SREL3)
- ❑ Used together with SmartStick AX with LSM 3.5 SPI and higher

// **TECHNICAL DATA**

LSM Mobile	System requirements
<ul style="list-style-type: none"> ❑ Simple programming software in System 3060 ❑ Programming, clock-setting, read-out, emergency opening ❑ SmartCD.G2, SmartCD2.G2, SmartCD.MP, SmartStick AX ❑ G1, G2 and AX locking devices ❑ Limited user rights possible ❑ Programming tasks prepared in the main software 	<ul style="list-style-type: none"> ❑ Screen: min. 20 cm (8 inches) ❑ Recommended screen resolution: 1920 x 1280 ❑ Suitable for touchscreen ❑ Processor: at least 1.6 GHz (Intel, AMD, no ARM) ❑ At least 1 GB RAM ❑ Hard disk size approx. 50 MB ❑ At least One USB port; two recommended ❑ MS Windows 10/11 (64-Bit)

PD.LSM-Mobile.EN – 2024.02