SKG-IKOB PRODUCTCERTIFICATE 443.632.01

Date of issue: 18-02-2019





Certificate holder

Simons Voss Technologies GmbH Feringastraße 4

D-85774 Unterföhring

T: +49 (0) 89 99 22 80 E: info@simons-voss.de

I: www.simons-voss.de

Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

long plate with electro mechanical handle link

delivered under logo / brand:

Simons Voss

delivered under type- and / or article number:

SH AS (option) C 00 1 yK z a DP , SH AS (option) D 00 1 yK z a DP option: SI

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

ir. H.A.J. van Dartel Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual. This certificate contains 2 pages.

SKG-IKOB Certificatie Poppenbouwing 56 4191 NZ Geldermalsen

Postbus 202 4190 CE Geldermalsen

T 088-2440100 info@skgikob.nl www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Simons Voss Technologies GmbH

Number: 443.632.01 page 2 of 2

1. PRODUCT TYPE long plate with electro mechanical handle link security furniture

Torig plate with closure modifical name in

2. TECHNICAL SPECIFICATION

Operating: Mechanical and electronical operation

Construction: 1 set of an outside part and an inside part with mounting screws

System: No cylinder hole

various handles

Material: out- and inside: zinc coated steel with inox cover

Dimension: outside part: 230x59x19 mm

inside part: 230x59x25 mm

Fixing: 3x M5 in steel bus, c.o.c. 110/95 mm

Intended use: wood, PVC, metal

in combination with self-locking (multi-point)cylinder mortise lock

with emergency / panic function (EN179 / 1125)

If glass is used in the door element (incl. Side-bar), this

must at least comply with class P4A

3. DELIVERY

The delivery includes an installation instruction:

v1.0 / 01.2018 Art.-Nr BS11.990540

4. PERFORMANCES

A long plate with electro mechanical handle link according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this long plate with electro mechanical handle link is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with
respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are
fulfilled.

A window or door, in existing buildings, in which this long plate with electro mechanical handle link is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

• the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).