

SKG-IKOB PRODUCTCERTIFICATE 443.393.02

Date of issue: 27-05-2016



Certificate holder

Simons Voss Technologies GmbH
Feringastrasse 4
D-85774 Unterföhring
T: +49 (0) 89 99 22 80
F: +49 (0) 89 99 22 82 22
E: info@simons-voss.de
I: www.simons-voss.de



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

euro profile cylinder with non lockable knob electro mechanical

delivered under logo / brand:

SimonsVoss

delivered under type- and / or article number:

Z4.(type)-(option).FD.TS.SKG , Z4.(type)-(option).FD.ZK.TS.VDS, type: AP2 , DM , MH option: FH , MR , WN , WNM , G2 , MS , WP , MR , ZK

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script that starts with a large loop and ends with a horizontal line.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Simons Voss Technologies GmbH
Number: 443.393.02

page 2 of 2

1. PRODUCT

euro profile cylinder with non lockable knob electro mechanical

MAIN GROUP

cylinder

2. TECHNICAL SPECIFICATION:

Construction: single or double with on both sides a knob

Operating / System: knob with full length plug, coupled with de cam by electronic operation

Material: cylinder body: brass with various coatings

Dimension: 17 mm profile from 60 mm in various extensions per 5 mm

Fixing: 1 steel bolt M5, length \geq backset + 10 mm

Intended use: in combination with cylinder mortice locks and security furniture + anti manipulation supply

3. DELIVERY

The delivery includes an installation instruction:

Z4.xx-yy.ZK.VDS Blatt 1/2 V2011-06

4. PERFORMANCES

A euro profile cylinder with non lockable knob electro mechanical according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro profile cylinder, with non lockable knob, electro mechanical is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled. Remark: In façade elements in accordance with a burglar resistance class (RC) of EN 1627 only SKG*** cylinders are applicable.

A window or door, in existing buildings, in which this euro profile cylinder, with non lockable knob, electro mechanical is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
-